

## UltraStudio Recorder 3G



Get the world's smallest pocket sized SDI and HDMI video capture for your Thunderbolt 3 laptop or desktop computer! UltraStudio Recorder 3G features the highest quality 10 bit uncompressed and compressed video capture that's compatible with all popular video software including DaVinci Resolve, Avid Media Composer, Adobe Premiere Pro CC and hundreds more!

\$115

#### Connections

#### **SDI Video Inputs**

1

#### **SDI Rates**

270Mb, 1.5G, 3G

#### **SDI Audio Inputs**

16 Channels embedded in SD/HD

#### **HDMI Video Inputs**

1

## **HDMI Audio Inputs**

8 Channels embedded in SD/HD

#### **Computer Interface**

Thunderbolt™ 3 (Mac OS, Windows and Linux)







## **Supported Codecs**

AVC-Intra, AVCHD, Canon XF MPEG2, Digital SLR, DV-NTSC, DV-PAL, DVCPRO50, DVCPROHD, DPX, HDV, HEVC, XDCAM EX, XDCAM HD, XDCAM HD422, DNxHR & DNxHD, Apple ProRes 4444, Apple ProRes 422 HQ, Apple ProRes 422, Apple ProRes 422 LT, Apple ProRes 422 Proxy, Uncompressed 8-bit 4:2:2, Uncompressed 10-bit 4:2:2, Uncompressed 10-bit 4:4:4.

### Software

#### Software Included

Media Express, Disk Speed Test, LiveKey, Blackmagic Desktop Video Utility and Blackmagic driver on Mac OS and Windows. Media Express, Blackmagic Desktop Video Utility and Blackmagic driver on Linux.

#### Internal Software Upgrade

Firmware built into software driver. Software driver loads upgrades at system start or via updater software.

## Software Applications





vMix



OB9

#### Other supported applications include:

Cinegy Capture Pro, DevTek EasyMediaSuite, Glookast Capturer, Livestream Producer, Metus Ingest, Softron MovieRecorder, ToolsOnAir just:in,

Burst Video WebClip2Go & [REC]Marker, Zoom.

## SDI Video Standards

#### **SD Video Standards**

525i59.94 NTSC, 625i50 PAL

#### **HD Video Standards**

720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60 1080PsF23.98, 1080PsF24, 1080PsF25, 1080PsF29.97, 1080PsF30 1080i50, 1080i59.94, 1080i60

#### 2K Video Standards

2Kp23.98 DCI, 2Kp24 DCI, 2Kp25 DCI, 2Kp29.97 DCI, 2Kp30 DCI, 2Kp50 DCI, 2Kp59.94 DCI, 2Kp60 DCI 2KPsF23.98 DCI, 2KPsF24 DCI, 2KPsF25 DCI, 2KPsF29.97 DCI, 2KPsF30 DCI

#### **SDI Compliance**

SMPTE 259M, SMPTE 274M, SMPTE 296M, SMPTE 424M and SMPTE 425M A/B

#### SDI Metadata Support

RP 188/SMPTE 12M-2 and closed captioning.

#### **SDI Audio Sampling**

Television standard sample rate of 48 kHz and 24-bit.

#### **SDI Video Sampling**

4:2:2, 4:4:4

#### **SDI Color Precision**

8, 10, 12-bit RGB 4:4:4 up to 1080p30, and 8, 10-bit YUV 4:2:2 in all standards.

#### **SDI Color Space**

REC 601, REC 709 and REC 2020

#### Multiple Rate Support

SDI video connection is switchable between SD and HD.

## **HDMI Video Standards**

#### **SD Video Standards**

525i59.94 NTSC, 625i50 PAL

#### **HD Video Standards**

720p50, 720p59.94, 720p60 1080p23.98, 1080p24, 1080p25, 1080p29.97, 1080p30, 1080p50, 1080p59.94, 1080p60 1080i50, 1080i59.94, 1080i60

#### **HDMI Audio Sampling**

Television standard sample rate of 48 kHz and 24 bit.

#### **HDMI Video Sampling**

4:2:2 and 4:4:4

#### **HDMI Color Precision**

8-bit RGB 4:4:4, 8-bit YUV 4:4:4 and 12-bit YUV 4:2:2 in all standards.

### **HDMI Configuration**

HDMI 2.0a supports Deep Color.

## **HDMI Color Space**

REC 601, REC 709 and REC 2020

#### **Multiple Rate Support**

HDMI video connection is switchable between SD and HD.

#### **Copy Protection**

HDMI input is unable to capture from copy protected HDMI sources. Always confirm copyright ownership before capture or distribution of content.

## Hardware Frame Buffer

v210 (10 bit YUV), 2vuy (8 bit YUV), ARGB, BGRA (8 bit RGB), r210 (10 bit RGB), R12B, R12L (12 bit RGB).

## Processing

## **Colorspace Conversion**

Hardware based real time.

## **Physical Installation**

Requires computer with a Thunderbolt™ 3 USB-C port. Please check support pages to see the full system requirements.

## **Physical Specifications**





# Operating Systems



Mac 11.1 Big Sur, Mac 12.0 Monterey or later.



Windows 8.1, 10 and 11, all 64-bit.



Linux

## Power Requirements

Powered by Thunderbolt cable. Requires computer with a Thunderbolt™ 3 USB-C port.

# **Environmental Specifications**

Operating Temperature

5° to 40° C (32° to 104° F)

Storage Temperature

-20° to 45° C (-4° to 113° F)

**Relative Humidity** 

0% to 90% non-condensing

What's Included

UltraStudio Recorder 3G

## Warranty

12 Month Limited Manufacturer's Warranty.

	uties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You car pt out at any time by changing cookie settings. Privacy Policy	
Blackmagic Design Authorized Reseller		

All items on this website are copyright Blackmagic Design Pty. Ltd. 2021, all rights reserved. All trademarks are property of their respective owners. MSRP includes