

Blackmagic Streaming Decoder 4K



Blackmagic Streaming Decoder 4K is a professional streaming decoder that lets you receive an H.264 or H.265 stream from Blackmagic Streaming Encoder, ATEM switcher or Blackmagic camera and convert it back to SDI and HDMI video. Includes Blackmagic Cloud streaming and 12G-SDI reference input that lets you connect SDI tally, camera control and talkback back to the encoder.

\$745

Connections

SDI Reference Inputs

1

SDI Video Outputs

1

SDI Reference Outputs

1

SDI Rates

1.5G, 3G, 6G, 12G

HDMI 2.0 Video Outputs

1

Frame Rate and Format Converters

On 12G-SDI Out and 4K HDMI Out.

Live Stream Audio Inputs / Outputs

2 channels embedded Live Stream audio on output.

2 channels embedded Program audio on input.

2 channels embedded talkback audio on input.

SDI Audio Inputs

16 channels embedded audio on 12G-SDI Ref In.

SDI Audio Outputs

16 channels embedded audio on 12G-SDI Ref Out.

16 channels embedded audio on 12G-SDI Out.

HDMI Audio Outputs


8 channels embedded audio on Monitor Out.

Webcam Outputs

1 x USB-C up to 2160p60

Ethernet

Ethernet supports 10/100/1000 BASE-T for live streaming, configuration and software updates.



Standards

HD Video Input Standards

720p50, 720p59.94, 720p60,
1080i50, 1080i59.94, 1080i60,
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60,

Ultra HD Video Input Standards

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

SDI Compliance

SMPTE 292M, SMPTE 296M,
SMPTE 424M, SMPTE 425M
level A and B, SMPTE 2081-1,
SMPTE 2081-10, SMPTE 2082-1,
SMPTE 2082-10, SMPTE 2084 and
SMPTE 2108-1.

Video Input Color Space

Rec. 709, Rec. 2020

3G SDI

Auto detects SMPTE level A or B on
SDI input.

HDMI HD Video Standards

720p50, 720p59.94, 720p60
1080i50, 1080i59.94, 1080i60
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60

HDMI Ultra HD Video Standards

2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

HDMI 4K Video Standards

4Kp23.98 DCI, 4Kp24 DCI, 4Kp25 DCI,
4Kp29.97 DCI, 4Kp30 DCI, 4Kp50 DCI,
4Kp59.94 DCI and 4Kp60 DCI

HDMI Color Precision

4:2:2

HDMI Color Space

YUV

Video Streaming Standards

720p25, 720p30, 720p50, 720p60,
1080i50, 1080i59.94, 1080i60,
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60,
2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

Video Output Conversion

12G-SDI Out and 4K HDMI Out can
follow the streaming standard or be
user configured to convert to any of
the following standards:

720p25, 720p30, 720p50, 720p60,
1080i50, 1080i59.94, 1080i60,
1080p23.98, 1080p24, 1080p25,
1080p29.97, 1080p30, 1080p50,
1080p59.94, 1080p60,
2160p23.98, 2160p24, 2160p25,
2160p29.97, 2160p30, 2160p50,
2160p59.94, 2160p60

HDR Metadata Support

Hybrid Log-Gamma, ST2084 300,
ST2084 500, ST2084 800, ST2084
1000, ST2084 2000, ST2084 4000,
ST2084.

Streaming

Direct Streaming

Receives (RTMP) H.264 or (SRT) H.265 streams from the Blackmagic Streaming Encoder or compatible Blackmagic cameras.

Closed Captions

Web Presenter 4K supports embedding CEA-608 and CEA-708 closed captions in your live RTMP stream.

Timecode

Support source timecode over RTMP and SRT streams on 12G-SDI Out.

Control

Control Panel

Built in control panel including 6 buttons, spin knob control and 2.2 inch color display.

Device Control

Front panel, USB-C or Ethernet.

External Control

Supports remote camera control, color corrector, tally and talkback. REST API over Ethernet for external control via HTTP when used with REST client applications.

Displays

Built in 2.2 inch LCD for monitoring video, audio and status plus menu settings.

Software

Compatible Services and Software

Facebook, Twitch, YouTube, Twitter, Restream.IO, Vimeo, BoxCast, Castr, AfreecaTV, Bilibili, DouYu, Weibo, Zoom, Skype, Microsoft Teams, QuickTime Player, FaceTime, OBS Studio, Open Broadcaster, VLC, Wirecast Play, Wowza Streaming Engine.

Operating Systems



Mac 13.0 Ventura,
Mac 14.0 Sonoma or later.



Windows 10, 64-bit.
Windows 11.



Linux



Chrome OS

Power Requirements

Power Supply	12V DC Input	Power Usage
1 x Internal 100 - 240V AC.	1 x 4-pin XLR for +12V DC input for external power supply or battery use.	TBA

Physical Installation

Physical Installation
One third rack unit width, 1 rack unit height.

Physical Specifications



Environmental Specifications

Operating Temperature	Storage Temperature	Relative Humidity
0° C to 40° C (32° - 104°F)	-20° to 45° C (-4° to 113° F)	0% to 90% non-condensing

What's Included

Blackmagic Streaming Decoder 4K
Welcome wallet with QR code for software download

Warranty

1 Year Limited Manufacturer's Warranty.

All items on this website are copyright Blackmagic Design Pty. Ltd. 2025, all rights reserved. All trademarks are property of their respective owners. MSRP includes duties, but excludes sales tax and shipping costs. This website uses remarketing services to advertise on third party websites to previous visitors to our site. You can opt out at any time by changing cookie settings. [Privacy Policy](#)

Blackmagic Design Authorized Reseller